



1 / 2 0

FIG. 1



2 / 2 0

F I G. 2



3 / 2 0

F I G. 3




FIG. 4




FIG. 5






FIG. 6




7 / 2 0

FIG. 7 A



APERTURE 140 mm
(CENTER SHIELD RATE OF 0 %)
(INPUT IS DELTA FUNCTION:
SIMULATE THE CASE OF ONE TRACER)

FIG. 7 D




APERTURE 140 mm
(CENTER SHIELD RATE OF 0 %)
(WHEN FOCUS IS SHIFTED)

FIG. 7 B




APERTURE 140 mm
(CENTER SHIELD RATE OF 35 %)

FIG. 7 E




APERTURE 140 mm
(CENTER SHIELD RATE OF 35 %)
(WHEN FOCUS IS SHIFTED)

FIG. 7 C




APERTURE 140 mm
(CENTER SHIELD RATE OF 50 %)

FIG. 7 F



APERTURE 140 mm
(CENTER SHIELD RATE OF 50 %)
(WHEN FOCUS IS SHIFTED)

FIG. 7 G



APERTURE 70 mm
(CENTER SHIELD RATE OF 0 %)

FIG. 8A




APERTURE 140 mm (CENTER SHIELD RATE OF 0 %)
(SIMULATION OF THE CASE OF IMAGING WITH CCD CAMERA)

FIG. 8B




APERTURE 140 mm (CENTER SHIELD RATE OF 35 %)
(SIMULATION OF THE CASE OF IMAGING WITH CCD CAMERA)

FIG. 8C



APERTURE 140 mm (CENTER SHIELD RATE OF 50 %)
(SIMULATION OF THE CASE OF IMAGING WITH CCD CAMERA)

FIG. 9A




STANDARD IMAGE

FIG. 9D




APERTURE 140 mm
(CENTER SHIELD RATE OF 50 %)

FIG. 9B




APERTURE 140 mm
(CENTER SHIELD RATE OF 0 %)

FIG. 9E




APERTURE 70 mm
(CENTER SHIELD RATE OF 0 %)

FIG. 9C



APERTURE 140 mm
(CENTER SHIELD RATE OF 35 %)

FIG. 9F




APERTURE 250 mm
(CENTER SHIELD RATE OF 50 %)

FIG. 10A




ORIGINAL IMAGE

FIG. 10C



APERTURE 140 mm
(CENTER SHIELD RATE OF 35 %)

FIG. 10B




APERTURE 140 mm
(CENTER SHIELD RATE OF 0 %)

FIG. 10D




APERTURE 140 mm
(CENTER SHIELD RATE OF 50 %)

FIG. 11A




ORIGINAL IMAGE

FIG. 11D




APERTURE 140 mm
(CENTER SHIELD RATE OF 50 %)

FIG. 11B




APERTURE 140 mm
(CENTER SHIELD RATE OF 0 %)

FIG. 11E



APERTURE 70 mm
(CENTER SHIELD RATE OF 0 %)

FIG. 11C



APERTURE 140 mm
(CENTER SHIELD RATE OF 35 %)

FIG. 12





FIG. 13



13/20

FIG. 14



FIG. 15




FIG. 16




FIG. 17






FIG. 18



PROSTAR 3.10


17-MAR-04
VEL COMP VW
M/S
TIME = 150.000
LOCAL MX = 20.26
LOCAL MN = 0.2499E-03
PRESENTATION GRID

17.50
16.25
15.00
13.75
12.50
11.25
10.00
8.750
7.500
6.250
5.000
3.750
2.500
1.250
0.0000



The Prediction of Heat and Flow around a Chimney (CASE2)
SEC1

FIG. 19



18 / 20

FIG. 20





FIG. 21



**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☐ FADED TEXT OR DRAWING
- ☒ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☐ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.